

# FlameSpec IR3 CO2L

Triple IR Flame Detector



The FlameSpec IR3 will detect fires and explosions extremely quickly, thereby allowing mitigation steps to be initiated more rapidly to limit event escalation.

## Introduction

The FlameSpec-IR3 CO2L flame detector has been optimized to provide a fast, robust detection of a wide range of heavy hydrocarbon fires, where combustion exhaust gases may be present, and standard IR3 detectors might false alarm.

Typical applications include:

- Aircraft hangars
- Hardened aircraft shelters
- Helipads (Onshore, Offshore, Hospitals)
- Areas with high vehicle activity:
  - Waste recycling facilities
  - Road / Rail tanker loading racks

## Key Benefits

- Highest levels of false alarm immunity.
- Detects up to 262 ft. (80m) for a 1 ft<sup>2</sup> (0.1m<sup>2</sup>) n-heptane pan fire.
- Hydrocarbon flame detection. Three wavelengths, in the infrared spectral range of 4.0 to 5.0  $\mu\text{m}$ , with clear separation.
- Each sensor has the same field of view to further improve false alarm immunity.
- Ultra-fast detection mode – detection within 40 milliseconds for fireballs or explosions.
- Fast flame detection, <1.5 s for standard fire up to 30 m.
- 5 selectable sensitivity levels.
- Universal outputs, 3 and 4 wire, 4-20 mA sink / source, Fire, Auxiliary and Fault Relays. RS485 port using Modbus RTU.
- Event logger – alarms & faults are logged to non-volatile memory.
- Built-in-Test (BIT) – Automatic and manual self-test of window cleanliness and overall detector operation.
- Dirty optics warning for preventive maintenance needs.
- HART® 7, as standard. Enhanced configuration & maintenance.
- Window heater to avoid condensation and icing.
- Stainless steel tilt mount provides horizontal and vertical adjustment.
- Functional safety - SIL 2 capable.

# FlameSpec-CO2L

## Triple IR Flame Detector

Model: FLS-IR3 CO2L

### Response Characteristics

Fuel	Size	Sensitivity	Distance ft. (m)	Avrg Resp. Time (s)
n-Heptane	1 x 1 ft.	Extreme	262 (80)	4.6
n-Heptane	1 x 1 ft.	High	197 (60)	3.7
n-Heptane	1 x 1 ft.	Medium	98 (30)	1.1
n-Heptane	1 x 1 ft.	Low	49 (15)	1.4
n-Heptane	1 x 1 ft.	Very Low	24.5 (7.5)	1.1
Diesel	1 x 1 ft.	Extreme	164 (50)	3.6
Diesel	1 x 1 ft.	Medium	79 (24)	3.2
Gasoline	1 x 1 ft.	Extreme	230 (70)	3.6
Gasoline	1 x 1 ft.	Medium	98 (30)	1.5
Isopropanol (IPA)	1 x 1 ft.	Extreme	180 (55)	2.8
Isopropanol (IPA)	1 x 1 ft.	Medium	75 (23)	1.2
JP5	2 x 2 ft.	Extreme	262 (80)	11
JP5	1 x 1 ft.	Extreme	164 (50)	3.6
JP5	1 x 1 ft.	High	148 (45)	3.5
JP5	2 x 2 ft.	Medium	148 (45)	3.5
JP5	1 x 1 ft.	Medium	82 (25)	1.5
JP5	1 x 1 ft.	Low	39 (12)	1.5
JP5	1 x 1 ft.	Very Low	20 (6)	1.3
Kerosene	1 x 1 ft.	Extreme	164 (50)	3.8
Kerosene	1 x 1 ft.	Medium	82 (25)	1.6
Lithium Ion Battery	5 cells 3.7 V 1.5 AH	Extreme	49 (15)	4.9
Lithium Ion Battery	5 cells 3.7 V 1.5 AH	Medium	33 (10)	3.6
Polypropylene	1 x 1 ft.	Extreme	115 (35)	3.3
Polypropylene	1 x 1 ft.	Medium	66 (20)	2.1
Wood	1 x 1 ft.	Extreme	131 (40)	5.0
Wood	1 x 1 ft.	Medium	66 (20)	1.2

# FlameSpec-CO2L

## Triple IR Flame Detector

### Immunity to False Alarm

Model: FLS-IR3 CO2L

False Alarm Source	Modulated		Unmodulated	
	Distance ft. (m)	Response	Distance ft. (m)	Response
Sunlight, (direct or reflected)	No response		No response	
Sunlight, (direct or reflected) with water droplets on sensors	No response		No response	
Incandescent frosted glass light, 300W	2.0 (0.5)	No Alarm	2.0 (0.5)	No Alarm
Fluorescent, 70W (3x23.3W)	2.0 (0.5)	No Alarm	2.0 (0.5)	No Alarm
Electric arc	2.0 (0.5)	No Alarm	2.0 (0.5)	No Alarm
Arc welding	12.0 (3.5)	No Alarm	12.0 (3.5)	No Alarm
Radiation heater, 1850W	2.0 (0.5)	No Alarm	2.0 (0.5)	No Alarm
Radiation heater, 1850W with water droplets on the sensors	2.0 (0.5)	No Alarm	2.0 (0.5)	No Alarm
Quartz lamp (1000W) shielded	2.0 (0.5)	No Alarm	2.0 (0.5)	No Alarm
Quartz lamp (500W) non-shielded	2.0 (0.5)	No Alarm	2.0 (0.5)	No Alarm
Mercury vapor lamp 160Wx3	2.0 (0.5)	No Alarm	2.0 (0.5)	No Alarm
Car exhausts	2.0 (0.5)	No Alarm	2.0 (0.5)	No Alarm
Projector led	2.0 (0.5)	No Alarm	2.0 (0.5)	No Alarm
Solenoid bell	2.0 (0.5)	No Alarm	2.0 (0.5)	No Alarm
Soldering iron	2.0 (0.5)	No Alarm	2.0 (0.5)	No Alarm
Electric drill	2.0 (0.5)	No Alarm	2.0 (0.5)	No Alarm

# FlameSpec-CO2L

## Triple IR Flame Detector

Model: FLS-IR3 CO2L

FIRE DETECTION	<b>Detection time and distance</b>	40ms for fast fire burst or explosion 1.5s for 1 ft <sup>2</sup> (0.1m <sup>2</sup> ) n-heptane pan fire at 0–100 ft. (0–30m) 4s for 1 ft <sup>2</sup> (0.1m <sup>2</sup> ) n-heptane pan fire at 100–262 ft. (30–80m)
	<b>Sensitivity range</b>	5 sensitivity ranges: Extreme, High, Medium, Low, Very Low
	<b>Field of view (IR detection)</b>	90° Horizontal, 80° Vertical
	<b>Time Delay</b>	Configurable 0-30 seconds
	<b>Built in Test</b>	Automatic and Manual
ELECTRICAL SPECIFICATIONS	<b>Operating Voltage</b>	24 VDC nominal (18-32 VDC)
	<b>Current Consumption</b>	Standby: 120mA 180mA all systems in operation (including window heater)
	<b>Electrical Entries</b>	2x cable and conduit entries 3/4" NPT(F) or M25x1.5
	<b>Wiring</b>	14-17 AWG (2.5–1.0 mm <sup>2</sup> )
OUTPUTS	<b>Relays</b>	SPST volt-free contacts rated 2A at 30 VDC 3 relays: Alarm & Auxiliary – normally open; Fault– normally closed
	<b>0-20mA (stepped) current output</b>	3 wire and 4 wire (isolated) configurations (sink and source) HART® rev 7.0
	<b>Indication</b>	Tri-color LED (Green, Yellow, Red)
	<b>Modbus</b>	RTU compatible on RS-485
MECHANICAL SPECIFICATIONS	<b>Size</b>	5.83 x 4.65 x 4.65" (148 x 118 x 118 mm)
	<b>Weight</b>	Detector (Stainless Steel 316): 6.6 lbs. (3.0 kg) Tilt mount (Stainless Steel 316): 3.3 lbs. (1.5 kg)
ENVIRONMENTAL SPECIFICATIONS	<b>Temperature Range</b>	Operating: -67°F to +185°F (-55°C to +85°C) Storage: -67°F to +185°F (-55°C to +85°C)
	<b>Humidity</b>	Up to 99% (RH), non-condensing
	<b>Ingress Protection</b>	IP66 & 68; NEMA 4X & 6P
APPROVALS	<b>ATEX</b>	ATEX: II 2 G D Ex db IIC T6 Gb or Ex db eb IIC T6 Gb and Ex tb IIIC T80°C Db -55°C<Ta<60°C Ex db IIC T5 Gb or Ex db eb IIC T5 Gb and Ex tb IIIC T95°C Db -55°C<Ta<75°C Ex db IIC T4 Gb or Ex db eb IIC T4 Gb and Ex tb IIIC T105°C Db -55°C<Ta<85°C
	<b>IECEX, INMETRO &amp; PESO</b>	Ex db IIC T5 Gb -50°C≤Ta≤75°C Ex db IIC T4 Gb -50°C≤Ta≤85°C Ex db IIC Gb T6 -50°C≤Ta≤60°C
	<b>FMus &amp; FMc</b>	Class I, Div. 1, Groups B, C & D; T4 Class I, Zone 1, AEx/Ex db IIC T4 Gb T4 -50°C≤Ta≤85°C; T5 -50°C≤Ta≤75°C; T6 -50°C≤Ta≤60°C
	<b>EAC CU TR</b>	1Ex d IIC T5 Gb or 1Ex de IIC T5 Gb and Ex tb IIIC T95°C Db -55°C≤Ta≤75°C 1Ex d IIC T4 Gb or 1Ex de IIC T4 Gb and Ex tb IIIC T105°C Db -55°C≤Ta≤85°C
	<b>Performance</b>	ANSI FM 3260 EN 54-10
	<b>Functional safety</b>	Certified SIL2 capable, per IEC 61508:2010 High & Low demand
ACCESSORIES	<b>Tilt mount, model FLS-TMO-S01</b>	<b>High vibration mounting bracket, model FLS-MIL-S01</b>
	<b>Weather cover, model FLS-WCO-S01</b>	<b>Flame simulator, model FLS-FSIM-IR3-KIT</b>
	<b>2" &amp; 3" pole mount adapter, model FLS-PMA-S23</b>	<b>Airshield, model FLS-ASD-S01</b>
	<b>Duct mount with window, model FLS-DMW-S01</b>	<b>Duct mount for airshield, model FLS-DMX-S01</b>
WARRANTY	5 years	